

	Nominal	Output	Wired
SPG-14	14.4V	XLR4 (1-Gnd, 4-Pwr)	Parallel
SPG-14A	14.4V	XLR4 (1-Gnd, 4-Pwr)	Parallel
SPG-28	28.8V	XLR3 (1-Gnd, 2-Pwr)	Series
SPG-28A	28.8V	XLR3 (1-Gnd, 2-Pwr)	Series

Call Our Sales Team

+44 (0) 1233 638715

Visit Us Online at

www.Hawkwoods.com



Hawk-Woods

Briscall house, Wotton Road Kingsnorth Industrial Estate Ashford, Kent, TN23 6LN, England 16mm Spigot Lighting Pole Instructions

Spigot Lighting Pole Series

Overview

The dual 16mm Spigot is available in varying voltages and battery fitting options offering a totally unique way to power LED/Panel lights.

General Use

The Spigot range has been designed to be compatible with the widely used 16mm lighting C-stands. Providing users with a lightweight portable solution allowing batteries to be attached conveniently below the LED/Panel light that require external power. Voltages available will be nominal 14.4V from either V-lok, Gold mount or 28.8V wired in series for lights requiring a larger DC input voltage.

Please check your equipment prior to use to ensure you have the correct product and are inputting the voltage that your equipment requires.



For more related products please go online to our website.



VL-HS1A Alexa Mini HotSwap



VL-ATM4 4-Channel Fast Charger



VL-CFA2Arri Amira
Cam Fitting